



## Sealer

## **CS45**

Automatic equipment for top and bottom sealing of boxes with adhesive tape or gummed paper (Meler/Melton). Features automatic adjustment to work alternately with different box sizes. This equipment includes top flap closing and is designed for integration into production lines. It is a robust and functional machine, ideal for any load weight.



Maximum box dimensions (external dimensions)         W mm           H mm         L mm           Minimum box dimensions (external dimensions)         W mm           H mm         H mm           Speed bands         m/min           TECHNICAL DATA           Weight         kg           L mm         W mm           H mm         Drag belts           Band height         mm           Working height         mm           SERVICE         Electrical voltage           Installed power         kW           Electrical consumption         kW/h           Air pressure         bar	500 450 400 250 210 200 20 400 2600 1255
(external dimensions)         H         mm           Minimum box dimensions (external dimensions)         W         mm           Speed bands         m/min           TECHNICAL DATA           Weight         kg           L         mm           Dimensions         W         mm           Drag belts         Band height         mm           Wide seal         mm           Working height         mm           SERVICE         Electrical voltage           Installed power         kW           Electrical consumption         kW/h	400 250 210 200 20 20 400 2600
H   mm   L   mm   W   mm   mm   mm   mm	250 210 200 20 20 400 2600
Minimum box dimensions (external dimensions)         W mm           H mm           Speed bands         m/min           TECHNICAL DATA           Weight         kg           L mm         W mm           H mm         H mm           Drag belts         Band height           Band height         mm           Working height         mm           SERVICE         Electrical voltage           Installed power         kW           Electrical consumption         kW/h	210 200 20 20 400 2600
(external dimensions)         V Minit           Speed bands         m/min           TECHNICAL DATA           Weight         kg           L         mm           W         mm           H         mm           Drag belts         mm           Wide seal         mm           Working height         mm           SERVICE           Electrical voltage         kW           Electrical consumption         kW/h	200 20 400 2600
Feed bands         m/min           TECHNICAL DATA           Weight         kg           L         mm           W         mm           H         mm           Drag belts         mm           Band height         mm           Wide seal         mm           Working height         mm           SERVICE         Electrical voltage           Installed power         kW           Electrical consumption         kW/h	20 400 2600
TECHNICAL DATA           Weight         kg           L mm         W mm           H mm         H mm           Drag belts         mm           Band height         mm           Working height         mm           SERVICE         Electrical voltage           Installed power         kW           Electrical consumption         kW/h	400 2600
Weight         kg           L mm         W mm           H mm         H mm           Drag belts         mm           Band height         mm           Working height         mm           SERVICE         Electrical voltage           Installed power         kW           Electrical consumption         kW/h	2600
Dimensions         L mm           W mm         H mm           Drag belts         mm           Band height         mm           Working height         mm           SERVICE         Electrical voltage           Installed power         kW           Electrical consumption         kW/h	2600
Dimensions  W mm H mm  Drag belts  Band height  Wide seal  Working height  SERVICE  Electrical voltage  Installed power  kW  Electrical consumption	
Drag belts  Band height mm  Wide seal mm  Working height mm  SERVICE  Electrical voltage  Installed power kW  Electrical consumption kW/h	1255
Drag belts  Band height mm  Wide seal mm  Working height mm  SERVICE  Electrical voltage  Installed power kW  Electrical consumption kW/h	
Band height mm  Wide seal mm  Working height mm  SERVICE  Electrical voltage  Installed power kW  Electrical consumption kW/h	1875
Wide seal mm  Working height mm  SERVICE  Electrical voltage  Installed power kW  Electrical consumption kW/h	Sides
Working height mm  SERVICE  Electrical voltage  Installed power kW  Electrical consumption kW/h	50
SERVICE  Electrical voltage  Installed power kW  Electrical consumption kW/h	50/70
Electrical voltage  Installed power kW  Electrical consumption kW/h	570/800
Installed power kW Electrical consumption kW/h	
Electrical consumption kW/h	230/400V III+N+T
	2
Air pressure bar	2
	6
Air consumption I/box	12,5
OPTIONS	
Bottom closure only version	0
3-flap closing guides	
Stainless steel	•