

# Tech\_M

THE PACKAGING MACHINERY BRAND



## Palletizing station **4AXIS**

Palletizing station for integration into automatic lines, adaptable to any type of rigid or semi-rigid packaging. It can handle a wide range of containers: boxes, bags, drums, and plastic containers. Thanks to its low maintenance and space optimization, 4AXIS equipment is the best option for palletizing in low to medium production lines.

MODEL		4AXIS
Maximum production	cicles/min.	8
Maximum load	kg	40
Accepted pallet sizes	L mm	800 - 1200
	A mm	600 - 1200
	H mm	max. 2400
Types of packaging accepted		Cardboard boxes Metal containers Plastic trays Cardboard trays Sacks Jugs
SERVICE REQUIREMENTS		
Pneumatic working pressure	bar	6
Air consumption	l/cicle	3
electrical voltage		230/400V III+N+T
Installed power	kW	6
Electrical consumption	kWh	4,8
TECHNICAL DATA		
Available heads		Suction plate Vacuum cups Grippers Forks
Head options		Interchangeable head Double head
Pallet position options		Floor Pallet truck conveyor Conveyor at 500 mm
Dimensions (pallet version h=1800 mm on ground)	L mm	2780
	A mm	1835
	H mm	4645
Approx. weight	kg	800