

Tech_M

THE PACKAGING MACHINERY BRAND



Wrapping machine **SPIN**

Automatic wrapping machines for unstable loads. Wrapping is carried out by the rotation of the arms while the load remains still. Designed to be integrated into production lines without any operator intervention. Fully customizable with a wide range of options and accessories, offering the perfect solution for every production requirement and working environment.

MODEL		SPIN
Max. output	pallets/h	60
Max. pallet dimensions	L mm	1200
	W mm	1200
	H mm	2000
Max. pallet weight	kg	2000
TECHNICAL DATA		
Film tension control		Motorized pre-stretch
Film cutting		Hot knife
Load heat sealing		●
Pre-stretch ratio		100-150-250%
Turntable speed control		●
Film carriage speed control		●
Maximum film width	mm	500
Film capacity (film diameter)	mm	260
Platform with motorized rollers		●
PLATAFORM		
Rotating element		Rotating arm
Rotation speed	RPM	30
Height	mm	500
Conveyor width	mm	940/1340
WEIGHT AND DIMENSIONS		
Weight	kg	2000
Dimensions	L mm	3990
	W mm	3390
	H mm	3680
SERVICE		
Pneumatic system	bar	6
Electrical voltage	V	230/400V III+N+T
Consumption	l/cycle	120
Electrical consumption	kWh	4
OPTIONS		
Maximum column height	mm	3400
Maximum platform diameter	mm	3000
Maximum load weight	kg	3000
Motorized top press for load stabilization		○
Top sheet dispenser COVERMATIC		○
Film cutter with blade		○
Safety fences		○
Strapping cord		○
Base risers		○
Double reel support		X
Adaptation to different environments and working temperatures		○
Stainless steel version		○
ANFID tape dispenser		X
RFID tag reader		○
JUMBO reels		○