

# Tech\_M

THE PACKAGING MACHINERY BRAND



## Bizzy/Bizzy+ Forming and Packing Monoblocs

Compact equipment for box forming and subsequent filling. Its modular design offers a wide range of installation options, making it adaptable to any type of workspace, no matter how small. The different head options available make these units a universal solution for any packing requirement.

| MODEL                             |             | BIZZY                                        | BIZZY+                    |
|-----------------------------------|-------------|----------------------------------------------|---------------------------|
| Maximum output                    | cycles/min* | 8                                            | 8                         |
| Maximum box dimensions (external) | L mm        | 600                                          | 650                       |
|                                   | W mm        | 410                                          | 410                       |
|                                   | H mm        | 400                                          | 400                       |
| Minimum box dimensions (external) | L mm        | 210                                          | 210                       |
|                                   | W mm        | 120                                          | 120                       |
|                                   | H mm        | 100                                          | 100                       |
| Supported box types               |             | RSC, HSC, FEFCO 0200/0201                    | RSC, HSC, FEFCO 0200/0201 |
| Available bottom closures         |             | tape, hot-melt glue                          | tape, hot-melt glue       |
| TECHNICAL DATA                    |             |                                              |                           |
| Available heads                   |             | flat vacuum, suction cups, tulips, clamps... |                           |
| Head options                      |             | double head, quick change                    |                           |
| Weight                            | kg          | 1250                                         | 1250                      |
| Dimensione                        | L mm        | 2385                                         | 3565                      |
|                                   | W mm        | 2770                                         | 3360                      |
|                                   | H mm        | 3790                                         | 3790                      |
| Working height                    | mm          | 650-750                                      | 650-750                   |
| SERVICE                           |             |                                              |                           |
| Electrical voltage                |             | 230/400v III+T+N                             | 230/400v III+T+N          |
| Installed power                   | kW          | 6,45                                         | 6,45                      |
| Electrical consumption            | kW/h        | 3,7                                          | 3,7                       |
| Air pressure                      | bar         | 6                                            | 6                         |
| Air consumption                   | l/cycle     | 12                                           | 12                        |
| OPTIONS                           |             |                                              |                           |
| Extended magazine                 |             | O                                            | O                         |
| Stainless steel                   |             | O                                            | O                         |

\*Depending on product characteristics